

Beyondtech PureGigabit ™ Fiber Patch Cables

BTPLCUSCU-0DC-XMXP

Beyondtech's high-quality LC to SC Fiber Patch Cable 9/125µm OS1 fiber is specially designed for fast Ethernet, Fiber Channel, Gigabit Ethernet Speeds, data center, premises, educational, LAN, SAN, commercial, 10GBASE-L (1310 nm), 10GBASE-E (1550 nm), 1000BASE-LX (1300 nm) and Asynchronous Transfer Mode (ATM) applications. It supports video, data and voice services.

FEATURES AND BENEFITS

- Our OS1 fiber patch cords conform with TIA/EIA 492AAAA and IEC60793-2-10 A1b standards and complies with RoHS specifications.
- Our OS1 cables have a 0.25 dB/km attenuation at 1550 nm and 0.35 dB/km at 1310 nm.
- This Single mode OS1 fiber patch cords operate at -20°C to +70°C and have a minimum installation bending radius of 5.0 cm and a minimum long term bending radius of 3 cm.
- OM1 patch cords allow for connections between
 patching panels and network and server equipment.
 OS1 9/125 patch cords are commonly used in passive
 applications (GPON, FTTX and LANs). (LC duplex
 connectors are joined with a plastic clip, easy to remove
 in case you need to separate the connectors.)



SPECIFICATIONS

Color Code: Yellow

Bend Radius: Minimum / 5cm

Cable Jacket: 3.0mm LSZH

Operating Temperature: -4° to 158° F (-20° to +70° C)


Core: OS1 9/125µm

Standard Zip Cord Duplex

Termination:Connector A (LC) / Connector B (SC)

Features:


Connectors feature dust caps on the tips for protection. LC and SC duplex assemblies are attached with easy-removable clips.







Example: BTPLCULCU0DC1M1P = Beyondtech | Patch Cables | LC | UPC | to LC | UPC | OS1 | Duplex | 3.0mm PVC | 1Meter | 1 Pack





For more information on Beyondtech Premium Warranty, visit beyondtech.us/warranty



DISCLAIMER


This datasheet is from authorship and exclusive property of Beyondtech. His reproduction is banned in the integral or partially without mentioning his authorship, as well as the alteration of his content or context.

IMPORTANT NOTICE

All statements, technical information, and recommendations related to Beyondtech products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in Beyondtech current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of Beyondtech.









SKU: BTPLCUSCU-0DC-XMXP

Name: LC to SC Singlemode Fibre Patch Cord Duplex - XM - UPC - 9/125 OS1um (LSZH) - Beyondtech Optical - PureOptics Cable Series

Cable Jacket: 3.0mm LSZH

Length (ft.): \times Length (m): \times

Connector type A: LC Connector type B: SC

Color: Yellow Core: OS1 9/125

WORLDWIDE CORPORATE HEADQUARTERS

Rediret UK LTD. London UK. info@rediret.com +44 (020) 3289.1190 Beyondtech Europe Madrid, ES info@beyondtech.es +34 (747) 869.449 Beyondtech Americas Miami, FL, USA info@beyondtech.global +1 (305) 897.3507 For more information, visit our website www.beyondtech.global, contact us at customer@beyondtech.global or call +1 (844) 283.5266 (toll-free).